



Main

Range	PowerLogic
Device short name	VLT
Product or component type	Voltmeter
Range compatibility	Prisma P door Prisma G door
Scale	0-500 V
Technology type	Ferromagnetic
Scale type	62 mm over 90°
Mounting support	Front face

Complementary

Type of measurement	Voltage
Accuracy class	Class 1.5
Power consumption in VA	3 VA
Power consumption in VA	3 VA
Overload withstand	1.2 Un, permanently 2 Un, 5 s
Device mounting	Flush
Operating position	30°/Vertical
Width	72 Mm
Height	72 Mm
Depth	75 Mm
Temperature drift	+/- 0.003 %/°C

Environment

Standards	IEC 61010-1 IEC 60051-1 IEC 61000-4
IP degree of protection	IP52
Ambient air temperature for operation	-25...50 °C
Reference temperature	23 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	215 G
Package 1 Height	8.5 Cm
Package 1 width	9 Cm
Package 1 Length	10 Cm

Unit Type of Package 2	S03
Number of Units in Package 2	33
Package 2 Weight	7.38 Kg
Package 2 Height	30 Cm
Package 2 width	30 Cm
Package 2 Length	40 Cm

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**