



Main

Range	PowerLogic
Device short name	VLT
Product or component type	Voltmeter
Range compatibility	Prisma P door Prisma G door
Scale	0-500 V
Technology type	Ferromagnetic
Scale type	80 mm over 90°
Mounting support	Front face

Complementary

Type of measurement	Voltage
Accuracy class	Class 1.5
Power consumption in VA	3 VA
Power consumption in VA	3 VA
Overload withstand	1.2 Un, permanently 2 Un, 5 s
Device mounting	Flush
Operating position	30°/Vertical
Width	96 Mm
Height	96 Mm
Depth	75 Mm
Temperature drift	+/- 0.003 %/°C

Environment

Standards	IEC 61000-4 IEC 60051-1 IEC 61010-1
IP degree of protection	IP52
Ambient air temperature for operation	-25...50 °C
Reference temperature	23 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	282 G
Package 1 Height	10.5 Cm
Package 1 width	11 Cm
Package 1 Length	11.5 Cm
Unit Type of Package 2	S03
Number of Units in Package 2	12
Package 2 Weight	3.83 Kg
Package 2 Height	30 Cm
Package 2 width	30 Cm
Package 2 Length	40 Cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**