## Product data sheet Characteristics

# 19000

NG125 - earth leakage add-on block - Vigi NG125 - 2P - 63A - 30mA





#### Main

Add-on residual current devices	
Vigi NG125	
2P	
63 A	
AC	
30 MA	
Instantaneous	
Type AC	
	Vigi NG125 2P 63 A AC 30 MA Instantaneous

#### Complementary

Complementary	
Device location in system	Outgoer
Network frequency	50/60 Hz
[Ue] rated operational voltage	230415 V AC 50/60 Hz
Residual current tripping technology	Voltage independent
[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	8 KV conforming to IEC 60947-2
Mounting support	35 mm symmetrical DIN rail
Electrical connection to mcb	By screws
9 mm pitches	5
Height	118 Mm
Width	99 Mm
Depth	81 Mm
Net weight	0.25 Kg
Electrical durability	10000 Cycles conforming to IEC 60947-2
Connections - terminals	Tunnel type terminals 135 mm² flexible Tunnel type terminals 1.550 mm² rigid
Wire stripping length	20 Mm
Tightening torque	3.5 N.M

### Environment

Standards	IEC 60947-2
IP degree of protection	IP40 conforming to IEC 60947-2
Pollution degree	3 conforming to IEC 60947-2
Electromagnetic compatibility	8/20 µs impulse withstand, 3000 A conforming to IEC 60947-2
Tropicalisation	2 conforming to IEC 60068-1

Relative humidity	95 % at 55 °C
Operating altitude	2000 m
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	328 G
Package 1 Height	9.4 Cm
Package 1 width	13.8 Cm
Package 1 Length	13.8 Cm
Unit Type of Package 2	S03
Number of Units in Package 2	8
Package 2 Weight	3.043 Kg
Package 2 Height	30 Cm
Package 2 width	30 Cm
Package 2 Length	40 Cm
Offer Sustainability	
Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual	warranty
-------------	----------

Warranty 18 months

Product Life Status : Commercialised

