

Antenna cable - RAD-CAB-EF393-15M - 2885634

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Antenna cable, outside diameter: 10 mm (0.4 in.), inner conductor: stranded, attenuation: 4.3 / 8.3 / 14.8 dB at 0.9 / 2.4 / 5.8 GHz, connection: 2 x N (male), cable length: 15 m (50 ft.)




The figure shows a version of the product

Your advantages

- For outdoor installation
- Easy installation, thanks to flexible inner conductor
- UV resistant
- Oil-resistant
- Halogen-free
- Flame-retardant



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 081573
GTIN	4046356081573

Technical data

Dimensions

Fixed cable length	15 m
External diameter	10.00 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 105 °C
Ambient temperature (storage/transport)	-40 °C ... 105 °C

General

Connection 1	Connector connection
Connection method	N (male)

Antenna cable - RAD-CAB-EF393-15M - 2885634

Technical data

General

Note	Both sides
Connection method	N (male)
Cable type	EF 393
Outer sheath, material	RADOX®(LSFH)
External sheath, color	black
Minimum bending radius	50.00 mm
Frequency range	0.3 GHz ... 6 GHz
Impedance	50 Ω

Attenuation

868 / 900 MHz	approx. 4.3 dB
2.4 GHz	8.3 dB
5 GHz	14.8 dB

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 25;
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 10.0.1	27060310
eCl@ss 4.0	27060800
eCl@ss 4.1	27060800
eCl@ss 5.0	27061800
eCl@ss 5.1	27061800
eCl@ss 6.0	27061800
eCl@ss 7.0	27061805
eCl@ss 8.0	27060310
eCl@ss 9.0	27060310

ETIM

ETIM 2.0	EC000019
ETIM 3.0	EC000019
ETIM 4.0	EC000019
ETIM 5.0	EC001682
ETIM 6.0	EC001682
ETIM 7.0	EC001682

Antenna cable - RAD-CAB-EF393-15M - 2885634

Classifications

UNSPSC

UNSPSC 6.01	26121608
UNSPSC 7.0901	26121608
UNSPSC 11	26121608
UNSPSC 12.01	26121608
UNSPSC 13.2	26121606
UNSPSC 18.0	26121606
UNSPSC 19.0	26121606
UNSPSC 20.0	26121606
UNSPSC 21.0	26121606

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		EAC-Zulassung
-----	-------------------------------------------------------------------------------------	---------------

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[2885634](#)