



## Main

Product name	UA
Product or component type	Control unit

## Complementary

[Us] rated supply voltage	220...240 V AC at 50/60 Hz
Operating mode	Forced operation on replacement source Stop (both normal and replacement source off) Automatic operation Forced operation on normal source
Interlocked device	Masterpact NW Compact NS100...630 Compact NS630b...1600 Masterpact NT
Selection modes	Circuit breaker on R Circuit breaker on N
Genset exerciser	Startup control Adjustable delayed shutdown
Test function	By pressing the test button on the front of the controller
Complementary function	Selection of type of normal source (single-phase or three-phase) Setting of maximum startup time for the replacement source Voluntary transfer to replacement source (e.g. energy management commands) Forced normal source if replacement source not operational during peak-tariff Additional contact: transfer to replacement source only if contact is closed
Local signalling	Fault trip On Off
Input type	Contacts customer voluntary order to transfer to source R
Output type	Contacts customer: indication of operation in automatic or stop mode
[Ith] conventional free air thermal current	8 A
[Ie] rated operational current	AC-12: 4 A AC 440 V AC-12: 5 A AC 380/415 V DC-13: 2 A 24 V

## Environment

Standards	IEC 947-5-1
IP degree of protection	IP20 connectors: conforming to EN 60529 IP40 front: conforming to EN 60529 IP30 side: conforming to EN 60529
IK degree of protection	Front: IK07 conforming to EN 50102

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.586 Kg
Package 1 Height	15.6 Cm
Package 1 width	15.6 Cm
Package 1 Length	18 Cm
Unit Type of Package 2	S04
Number of Units in Package 2	6
Package 2 Weight	10.282 Kg
Package 2 Height	30 Cm
Package 2 width	40 Cm
Package 2 Length	60 Cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : <b>Commercialised</b>
---