



Main

Device short name	MN delay unit
Product or component type	Time delay relay
Device application	Control
Range compatibility	MasterPact NT Masterpact NW ComPact NSX ComPact NS630b...1600 ComPact NS1600b...3200 PowerPact Multistandard ComPact NSXm ComPact NSX DC Masterpact NW UL 489 Masterpact NT UL 489 Masterpact NW DC
Voltage release type	Undervoltage release
[Uc] control circuit voltage	100...130 V AC 50/60 Hz 100...130 V DC

Complementary

Impulse duration	200 ms
Time delay range	0.5...3 s
Threshold tripping voltage	0.35...0.7 Un open 0.85 Un close
Supply holding power	4.5 VA
Supply inrush power	200 VA
Mounting mode	External mounting
Response time	0.5 s 1 s 1.5 s 3 s
Accessory / separate part category	Spare part for Compact NS630b...1600 Spare part for Compact NS1600b...3200

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	192 G
Package 1 Height	8.5 Cm
Package 1 width	8 Cm
Package 1 Length	9 Cm
Unit Type of Package 2	S03

Number of Units in Package 2	36
Package 2 Weight	7.31 Kg
Package 2 Height	30 Cm
Package 2 width	30 Cm
Package 2 Length	40 Cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**