



### Main

Device short name	MCH
Product or component type	Motor mechanism
Device application	Automatic spring charging
Range compatibility	ComPact NS630b...1600
Control type	Standard
[Uc] control circuit voltage	220...240 V AC 50/60 Hz
Mounting mode	Fixed
[In] rated current	630 A 1000 A 1600 A 800 A 1250 A

### Complementary

Control signal type	Impulse Maintained
Response time	60 ms +/- 10 ms open 60 ms +/- 10 ms closed
Maximum operating frequency	<= 3 cycles per minute
Maximum power consumption in VA	180 VA

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.193 Kg
Package 1 Height	15 Cm
Package 1 width	15 Cm
Package 1 Length	40 Cm
Unit Type of Package 2	S01
Number of Units in Package 2	1
Package 2 Weight	1.193 Kg
Package 2 Height	15 Cm
Package 2 width	15 Cm
Package 2 Length	40 Cm

## Offer Sustainability

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**