



Main

Product or component type	Rear connection
Accessory / separate part category	Connection accessory
Range compatibility	ComPact NS630b...1600 circuit breaker ComPact NS630b...1600 switch disconnecter MasterPact NT circuit breaker MasterPact NT switch disconnecter
Poles description	3P
[In] rated current	630 A H1 drawout 630 A H2 drawout 630 A H3 drawout 630 A L1 drawout 800 A H1 drawout 800 A H2 drawout 800 A H3 drawout 800 A L1 drawout 1000 A H1 drawout 1000 A H2 drawout 1000 A H3 drawout 1000 A L1 drawout 1250 A H1 drawout 1250 A H2 drawout 1250 A H3 drawout 1600 A H1 drawout 1600 A H2 drawout 1600 A H3 drawout 1600 A H2T drawout 630 A HA drawout 800 A HA drawout 1000 A HA drawout 1250 A HA drawout 1600 A HA drawout 1250 A HF drawout 630 A HF drawout

Complementary

Location of connection	Rear
Localisation on device	Upside
Connection position	Horizontal
Connection pitch	70 Mm

Packing Units

Package 1 Weight	2.038 Kg
Package 1 Height	0.150 Dm
Package 1 width	0.450 Dm
Package 1 Length	0.600 Dm

Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status :	Commercialised
-----------------------	-----------------------