



The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Main

Product or component type	Rear connection
Accessory / separate part category	Connection accessory
Range compatibility	Masterpact NW Masterpact NW20 switch disconnecter Masterpact NW Masterpact NW25 switch disconnecter Masterpact NW Masterpact NW32 switch disconnecter Masterpact NW Masterpact NW32 circuit breaker Masterpact NW Masterpact NW20 circuit breaker Masterpact NW Masterpact NW25 circuit breaker
Poles description	3P
[In] rated current	3200 A H1 drawout 3200 A H2 drawout 3200 A H3 drawout 3200 A H1 fixed 3200 A H2 fixed 3200 A L1 drawout 2000 A H3 drawout 2000 A L1 drawout 2500 A H1 drawout 2500 A H1T drawout 2500 A H2 drawout 2500 A H2A drawout 3200 A H1T drawout 3200 A H2A drawout 2500 A N1 fixed 2500 A H1 fixed 2500 A H2 fixed 2500 A H2A fixed 2500 A H1T fixed 2500 A L1 fixed 2500 A H1b fixed 2500 A N2 fixed 3200 A H2A fixed 3200 A H1T fixed 3200 A L1 fixed 3200 A H1b fixed 3200 A HA fixed 3200 A HF fixed 2500 A HA fixed 2500 A HF fixed 2500 A N1 drawout 2500 A L1 drawout 2500 A H1b drawout 2500 A N2 drawout 2500 A HA drawout 2500 A HF drawout 2500 A HA10 drawout 3200 A H1b drawout 3200 A HA drawout 3200 A HF drawout 3200 A HA10 drawout 2500 A HA10 fixed 3200 A HA10 fixed 2500 A H3 drawout 2500 A H10 drawout 3200 A H10 drawout

## Complementary

Location of connection	Rear
Localisation on device	Downside
Connection position	Horizontal
Connection pitch	115 Mm

### Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

### Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status :	<b>Commercialised</b>
-----------------------	-----------------------