



Main

Range	Acti9
Product name	Acti9 iCT
Product or component type	Contactor
Device short name	ICT
Device application	Motor-heating-lighting
Poles description	2P
[Ie] rated operational current	16 A AC-7A 6 A AC-7B
Pole contact composition	1 NO + 1 NC
Network type	AC
Control type	Remote control
[Uc] control circuit voltage	220...240 V AC 60 Hz

Complementary

Network frequency	60 Hz
[Ue] rated operational voltage	250 V AC 60 Hz
Maximum power	0.9 W at 250 V AC
[Ui] rated insulation voltage	500 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	4 KV
Control signal type	Maintained
Switching frequency	100 switching operations/day
Local signalling	Action indicator
Hold-in power consumption in VA	2.7 VA
Inrush power in VA	9.2 VA
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	81 Mm
Width	18 Mm
Depth	68.5 Mm
Colour	White
Mechanical durability	1000000 Cycles
Electrical durability	100000 Cycles IEC/EN 61095 16 A 60 Hz AC-7A 30000 Cycles IEC/EN 61095 6 A 60 Hz AC-7B 30000 Cycles IEC/EN 61095 60 Hz AC-7C 100000 Cycles EN/IEC 60947-4-1 60 Hz AC-1 30000 Cycles EN/IEC 60947-4-1 60 Hz AC-3 30000 Cycles EN/IEC 60947-4-1 60 Hz AC-5a 30000 Cycles EN/IEC 60947-4-1 60 Hz AC-5b

Connections - terminals	Control circuit: tunnel type terminals2 cable(s) 1.5 mm ² rigid Power circuit: tunnel type terminals1 cable(s) 1...4 mm ² flexible Power circuit: tunnel type terminals1 cable(s) 1.5...6 mm ² rigid Control circuit: tunnel type terminals1 cable(s) 1.5...2.5 mm ² rigid Control circuit: tunnel type terminals2 cable(s) 1.5...2.5 mm ² flexible
Tightening torque	Control circuit: 0.8 N.m Power circuit: 0.8 N.m
Product compatibility	IACTs
Compatibility code	ICT
Market segment	Residential Small commercial


Environment

Standards	IEC/EN 61095
Noise level	30 DB
Heat dissipation	0.9 W
IP degree of protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
Pollution degree	2
Tropicalisation	2 conforming to EN 60947-4-1 2 conforming to EN 61095 2 conforming to IEC 1095
Relative humidity	95 % at 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-5...60 °C
Ambient air temperature for storage	-40...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	117 G
Package 1 Height	1.8 Cm
Package 1 width	7.3 Cm
Package 1 Length	8.5 Cm
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Weight	1.469 Kg
Package 2 Height	10 Cm
Package 2 width	8 Cm
Package 2 Length	23 Cm
Unit Type of Package 3	S03
Number of Units in Package 3	144
Package 3 Weight	18.115 Kg
Package 3 Height	30 Cm
Package 3 width	30 Cm
Package 3 Length	40 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**