



Main

| | |
|------------------------------|---|
| Range | Prodis Acti 9 Librio Clario |
| Product or component type | OC contact |
| Device short name | OF |
| Signal contacts composition | 1 C/O |
| [In] rated current | 3 A: 380...415 V AC - 50/60 Hz 6 A: 220...240 V AC - 50/60 Hz 1 A: 130 V DC 1.5 A: 60 V DC 2 A: 48 V DC 6 A: 24 V DC |
| [Uc] control circuit voltage | 24...415 V AC 50/60 Hz 24...130 V DC |
| 9 mm pitches | 1 |

Complementary

| | |
|-------------------------|--|
| Range compatibility | Acti9 DPN Vigi Acti9 RCCB-ID Acti9 C60H-DC Acti 9 C60PV-DC Acti 9 C40 Acti9 ID C40 Acti 9 C120 Acti 9 DT40 Acti 9 DT60 Acti9 IDc Acti 9 C120NA-DC Acti 9 iDPN Acti9 ITG40 Acti 9 SW60-DC Acti 9 C60NA-DC |
| Mounting mode | Fixed |
| Mounting support | DIN rail |
| Height | 85.3 Mm |
| Width | 9 Mm |
| Depth | 73.5 Mm |
| Net weight | 30 G |
| Colour | White |
| Connections - terminals | Screw clamp terminal (bottom) 2 cable(s) 1.5 mm ² - flexible Screw clamp terminal (bottom) 1 cable(s) 0.5...2.5 mm ² - rigid Screw clamp terminal (bottom) 2 cable(s) 1.5 mm ² - flexible with ferrule |

| | |
|-----------------------|-------|
| Wire stripping length | 9 Mm |
| Tightening torque | 1 N.M |

Environment

| | |
|---------------------------------------|-------------------------------------|
| Standards | EN/IEC 60947-5-1 |
| Product certifications | ASEFA KEMA LCIE ASTA |
| IP degree of protection | IP20 conforming to EN/IEC 60947-5-1 |
| Pollution degree | 3 conforming to EN/IEC 60947-5-1 |
| Tropicalisation | 2 conforming to EN/IEC 60947-5-1 |
| Ambient air temperature for operation | -25...50 °C |
| Ambient air temperature for storage | -40...85 °C |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 38 G |
| Package 1 Height | 2 Cm |
| Package 1 width | 8 Cm |
| Package 1 Length | 9.4 Cm |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 12 |
| Package 2 Weight | 512 G |
| Package 2 Height | 8.7 Cm |
| Package 2 width | 10 Cm |
| Package 2 Length | 26.5 Cm |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 108 |
| Package 3 Weight | 5.088 Kg |
| Package 3 Height | 30 Cm |
| Package 3 width | 30 Cm |
| Package 3 Length | 40 Cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Product Life Status : **Commercialised**