



## Main

Range	Acti 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	1L + N
Total number of 18 mm modules	57

## Complementary

Number of ways	28 ways N + 1 L
Poles configuration for 1 way	1 x 1P + N 1 x 2P
Connection pitch	18 Mm
Connector type	Tooth
Distance between way	36 Mm
Marking	N L
Insulation	Insulated
Device presentation	Cuttable
Provided equipment	Set of 10 end piece
[Ie] rated operational current	100 A at 40 °C
[Ue] rated operational voltage	415 V AC
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-2
Mounting mode	Horizontal
Mounting location	Top or bottom on tunnel type terminals Top or bottom on double terminal
9 mm pitches	114
Width	1000 Mm
Colour	White (RAL 9003)
Range compatibility	Acti9 iC60 Acti9 iK60 Acti9 iLD Acti9 iLD K Acti9 iSW Acti9 iSW-NA Multi 9 C60

## Environment

Standards	IEC 60947-7-1 IEC 61439-2
Fire resistance	960 °C ( 30 s ) conforming to IEC 60695-2-1
Pollution degree	3 conforming to IEC 60947-7-1
IP degree of protection	IP20 with end-pieces and tooth covers

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	455 G
Package 1 Height	0.54 Cm
Package 1 width	0.9 Cm
Package 1 Length	104 Cm
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Weight	2.28 Kg
Package 2 Height	5.4 Cm
Package 2 width	105 Cm
Package 2 Length	9 Cm
Unit Type of Package 3	P12
Number of Units in Package 3	270
Package 3 Weight	135.12 Kg
Package 3 Height	112 Cm
Package 3 width	80 Cm
Package 3 Length	120 Cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**