



## Main

Range	Actassi
Product or component type	Patch panel
Device presentation	Loaded
Provided equipment	With shutter

## Complementary

[In] rated current	1.5 A
Number of port	24 port of UTP
Product compatibility	Standard 19" cabinet/rack
Communication network category	6
Contact resistance	1 MOhm
Insulation resistance	>= 200 MOhm
Minimum number of matings	1000 Cycles
Number of rack unit	1U
Type of footprint	S-110 keystone

## Environment

Ambient air temperature for operation	-40...70 °C
Standards	ANSI/TIA/EIA-568-B ISO/IEC 11801 Ed.2, 2002

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	990 G
Package 1 Height	1.77 Cm
Package 1 width	4.34 Cm
Package 1 Length	48.3 Cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**