ACTRJSMTG6ANSS

Actassi - modular jack - category 6A - 10G - FTP - non shuttered





Main

Range	Actassi	
Product brand	Schneider Electric	
Product or component type	Keystone modular jack	
Provided equipment	Without shutter	
Colour tint	Metal (zamak)	
Colour code	TIA-568A/B	
Type of packing	Plastic bag and carton	
Quantity per set	Set of 1	
Quantity per set	Set of 1	

Complementary

Complementary		
[In] rated current	1.5 A at 25 °C	
Permissible voltage	1000 V AC/DC peak, between contacts	
Contact resistance	20 MOhm	
Insulation resistance	>= 500 MOhm	
Connector type	RJ45	
Tool type	Punch down tool Quick termination tool	
Cable outer diameter	0.91.4 Mm	
Cable shielding type	STP	
Communication network category	6 _A	
Communication network type	10GBASE-T	
Product compatibility	RJ45 plug	
Type of footprint	S-110 keystone	
Targeted region	Asia Pacific.	

Environment

Ambient air temperature for operation	-1060 °C
Ambient air temperature for storage	-2070 °C
Relative humidity	093 %
Climatic withstand	40/070/21 (21 days)
Flame retardance	UL94-V0 conforming to UL listed
Product certifications	FCC part 68 F IEC 60603-7
Standards	ISO/IEC 11081 IEC 60603-7 ANSI/TIA/EIA-568-B

Packing Units

PCE
1
40 G
4 Mm
48 Mm
482 Mm
CAR
160
7.104 Kg
27 Cm
32 Cm
38 Cm
P12
2880
127.872 Kg
95 Cm
80 Cm
120 Cm

Offer Sustainability

oner edetamasmy		
Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

	Warranty	18 months
--	----------	-----------

Product Life Status : Commercialised