Product data sheet Characteristics

E8215_AS_G1 13A 250V 1Gang switched socket,Aluminium Silver





Main

Range	Pieno	
Product or component type	Power socket-outlet	
Device application	Power supply	
Switch function	Switch	
Rated current	13 A at 250 V AC 5060 Hz	
Number of gangs	1 gang	
Load type	Resistive	
Cover frame colour tint	Aluminium silver	

Complementary

Wiring device mounting	Surface Flush	
Material	Polycarbonate: surround Polycarbonate: grid plate	
Clamping connection capacity	2 x 4 mm² for stranded cable(s) 3 x 2.5 mm² for solid cable(s)	
Width	87 Mm	
Height	87 Mm	
Depth	26.6 Mm	

Environment

Ambient air temperature for operation	-540 °C
Relative humidity	095 %
Standards	SS 145-2 MS 589-2 BS 1363-2

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	107.983 G	
Package 1 Height	2.72 Cm	
Package 1 width	8.7 Cm	
Package 1 Length	8.7 Cm	
Unit Type of Package 2	CAR	
Number of Units in Package 2	80	

Package 2 Weight	8638.64 G
Package 2 Height	21 Cm
Package 2 width	32.5 Cm
Package 2 Length	50 Cm
Unit Type of Package 3	PAL
Number of Units in Package 3	1600
Package 3 Weight	189772.8 G
Package 3 Height	84 Cm
Package 3 width	82.5 Cm
Package 3 Length	100 Cm

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant E EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

Product Life Status : Commercialised