



Main

Product or component type	Electronic keycard reader
Rated current	16 A at 220...240 V AC 50/60 Hz
Load type	Resistive

Complementary

Material	Polycarbonate: surround Polycarbonate: grid plate
Wiring device mounting	Flush
Width	87 Mm
Height	87 Mm
Depth	9.1 Mm

Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Standards	IEC 60669-2-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	135 G
Package 1 Height	45 Mm
Package 1 width	87 Mm
Package 1 Length	87 Mm
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Weight	878 G
Package 2 Height	9.5 Cm
Package 2 width	15 Cm
Package 2 Length	19.5 Cm
Unit Type of Package 3	CAR
Number of Units in Package 3	60
Package 3 Weight	9.58 Kg
Package 3 Height	21 Cm

Package 3 width	32.5 Cm
Package 3 Length	50 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Product Life Status : **Commercialised**