



Main

Range of product	Pieno
Product or component type	Switch
Switch function	Intermediate
Switch application	Switch
Rated current	16 AX at 250 V AC 50 Hz
Local signalling	Fluorescent (white)
Number of gangs	1 gang
Load type	Resistive Fluorescent

Complementary

Wiring device mounting	Flush Surface
Material	Polycarbonate: surround Polycarbonate: grid plate
Connections - terminals	Pillar terminals
Clamping connection capacity	2 x 1.5 mm ² for stranded cable(s) 2 x 2.5 mm ² for solid cable(s)
Width	87 Mm
Height	87 Mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	GB 16915.1 IEC 60669-1
Product certifications	CCC

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	92 G
Package 1 Height	3.107 Cm
Package 1 width	8.428 Cm
Package 1 Length	8.594 Cm
Unit Type of Package 2	BB1

Number of Units in Package 2	10
Package 2 Weight	1.01 Kg
Package 2 Height	10 Cm
Package 2 width	18.9 Cm
Package 2 Length	20 Cm
Unit Type of Package 3	CAR
Number of Units in Package 3	60
Package 3 Weight	6.611 Kg
Package 3 Height	22.9 Cm
Package 3 width	30.5 Cm
Package 3 Length	39.9 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Product Life Status : **Commercialised**