



Main

Range of product	Pieno
Product or component type	Switch
Switch function	1-way
Switch application	Switch
Rated current	16 AX at 250 V AC 50 Hz
Local signalling	Fluorescent (white)
Number of gangs	2 gangs
Load type	Resistive Fluorescent

Complementary

Wiring device mounting	Flush Surface
Material	Polycarbonate: surround Polycarbonate: grid plate
Connections - terminals	Pillar terminals
Clamping connection capacity	2 x 1.5 mm ² for stranded cable(s) 2 x 2.5 mm ² for solid cable(s)
Width	87 Mm
Height	87 Mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	IEC 60669-1 GB 16915.1
Product certifications	CCC

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	95.55 G
Package 1 Height	3.55 Cm
Package 1 width	8.7 Cm
Package 1 Length	8.7 Cm
Unit Type of Package 2	BB1

Number of Units in Package 2	8
Package 2 Weight	764.4 G
Package 2 Height	9.5 Cm
Package 2 width	15 Cm
Package 2 Length	19 Cm
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Weight	7644 G
Package 3 Height	21 Cm
Package 3 width	32.5 Cm
Package 3 Length	50 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Product Life Status : **Commercialised**