

HYDRAULIC PIPE BENDER



EGA Master manufactures a wide range of pipe tools, such as CURVAMATIC hydraulic pipe benders. They are designed for bending steel pipes from 1/4 " up to 2" (Curvomatic 2") and from 1/4" up to 3 "(Curvomatic 3").

Two speeds and quick action!



Maximum stability!
 *G12: MONTHS OF WARRANTY

1. Specially designed to bend water, oil, gas...steel pipes, with maximum comfort and speed.



2. The double plate provides optimum consistency and safety during its operation.


3. The tool is anchored on a rotating tripod for maximum stability and ergonomy.

4. The special and innovative 2-VELO valve system enables fast pre-loading as well as a soft bending without any need to change pistons.

5. They are designed for bending pipes according to DIN-2440 and API standards.

CURVAMATIC 2" AND 3"



COD	∅	TONS	Kg.	
60015 Curvomatic 2"	1/4"-2"	10	75	1
60016 Curvomatic 3"	1/4"-3"	13	110	

Maximum degree of curvature 90°, two speeds and quick action

CURVAMATIC 2" and 3" WITH ANGLE MEASURER



With angle measurer

COD	Ø	TONS	Kg.	
56947 Curvamic 2"	1/4"-2"	10	75	1
56948 Curvamic 3"	1/4"-3"	13	110	1

Maximum degree of curvature 90°, two speeds and quick action

BENDING FORM



COD	Ø	R	Kg.	
64190	1/4", 3/8", 1/2"	86	0,8	1
64191	3/4"	108	1,1	
64192	1"	135	1,1	
64193	1.1/4"	170	2,4	
64194	1.1/2"	193	3,0	
64195	2"	242	5,0	
*64231	2.1/2"	303	16	
*64232	3"	358	22	

* For Curvamic 3" only

API NORM PIPE

Valido para / Valid for / Valable pour	Schedule 10		Schedule 40				Schedule 80				Schedule 160					
	I.D. mm	I.D. inch	mm	inch	I.D. mm	I.D. inch	mm	inch	I.D. mm	I.D. inch	mm	inch	I.D. mm	I.D. inch	mm	inch
1/4	10,4	0,41	1,65	0,065	9,22	0,364	2,24	0,088	7,66	0,302	3,02	0,119	No	No	No	No
3/8	13,8	0,545			12,48	0,493	2,31	0,091	13,84	0,423	3,20	0,126	standardized	standardized	standardized	standardized
1/2	17,08	0,674	2,11	0,083	15,76	0,622	2,77	0,109	13,84	0,546	3,73	0,147	11,74	0,464	4,78	0,188
3/4	22,48	0,884			20,96	0,824	2,87	0,113	18,88	0,742	3,91	0,154	15,58	0,612	5,56	0,219
1	27,86	1,097			26,64	1,049	3,38	0,133	24,3	0,957	4,55	0,179	20,70	0,815	6,35	0,25
1.1/4	36,66	1,442	2,77	0,109	35,08	1,38	3,56	0,14	32,5	1,278	4,85	0,191	29,50	1,16		
1.1/2	42,76	1,682			40,94	1,61	3,68	0,145	38,14	1,5	5,08	0,200	34,02	1,338	7,14	0,281
2	54,76	2,157			52,48	2,067	3,91	0,154	49,22	1,939	5,54	0,218	42,82	1,687	8,74	0,344
2.1/2	66,9	2,635	3,05	0,12	62,68	2,469	5,16	0,203	-	-	-	-	-	-	-	-
3	82,8	3,26			77,92	3,068	5,49	0,216	-	-	-	-	-	-	-	-

* For Curvamic 3" only

DIN-2440 STEEL PIPE

Ø	O.D.	Thickness mm.
1/4"	13	
3/8"	17	2.35
1/2"	21	
3/4"	27	2.65
1"	34	
1.1/4"	42	3.25
1.1/2"	48	
2"	60	
* 2.1/2"	76	3.65
* 3"	89	4.05

* For Curvamic 3" only