



IMPACT

SOCKET WRENCHES

EGA Master offers a wide range of impact sockets, available in short and long series. **The 4 and 8 pans socket wrenches are ideal for square nuts and screws.**


Made of **chrome-molybdenum steel**, which is the very best material for the manufacture of impact sockets as it provides the optimum relationship between hardness and resistance.

4 and 8 pans in inches

Designed for automotive applications, petrochemical and mining industry.



With the same wall thickness as conventional sockets, **impact sockets reach greater tightening forces.**



Cylindrical in design in order to provide **greater accessibility.**



IMPACT SOCKET WRENCHES 8 pans

1/2"



COD	AF	L	A	B	C	MINIMUM TIGHTENING TORQUE (lbf-in.)	MINIMUM TIGHTENING TORQUE (Nm/M)
56350	3/8"	19			6	1100	372
56351	7/16"	21	24		8	1500	507
56352	1/2"	24			9	2000	678
56353	9/16"	26	26			2600	882
56354	5/8"	28	28	11		3300	1119
56355	11/16"	30	30			4100	1389
56356	3/4"	34	34	13			
56357	13/16"	36	36		15		
56358	7/8"	38					
56359	15/16"	42	38		18	5000	1695
56360	1"	44					
56361	1.1/16"	46.5	46.5		19		
56362	1.1/8"	49	49				

ASME B107.2

IMPACT SOCKET WRENCHES 4 pans

3/4"



COD	AF	L	A	B	C	MINIMUM TIGHTENING TORQUE (lb-f-in.)	MINIMUM TIGHTENING TORQUE (Nm/M)
56394	5/8"		32			3300	1119
56395	11/16"	52	34	40	13	4100	1389
56396	13/16"		42	42	15	5000	1695

ASME B107.2

IMPACT SOCKET WRENCHES 8 pans

3/4"



COD	AF	L	A	B	C	MINIMUM TIGHTENING TORQUE (lb-f-in.)	MINIMUM TIGHTENING TORQUE (Nm/M)
56363	5/8"		32			3300	1119
56364	11/16"		34	40	13	4100	1389
56365	3/4"	50	40				
56366	13/16"		42	42	15		
56367	7/8"		44				
56368	15/16"	52	46		18		
56369	1"		50				
56370	1.1/16"		53				
56371	1.1/8"	54	56	44	19	5000	1695
56372	1.3/16"		58		21		
56373	1.1/4"		61		22		
56374	1.5/16"	56	63.5				
56375	1.7/16"		68		24		
56376	1.1/2"	58	70				

ASME B107.2

IMPACT SOCKET WRENCHES 4 pans

1"



COD	AF	L	A	B	C	MINIMUM TIGHTENING TORQUE (lb-f-in.)	MINIMUM TIGHTENING TORQUE (Nm/M)
56397	3/4"		43	52	13	6400	2169
56398	13/16"	57	44		15	7400	2508
56399	7/8"		48			8400	2847
56400	15/16"	60	50		18	9400	3186
56401	1"		53	54		10500	3558
56402	1.1/8"		60		19	12800	4338
56403	1.1/2"	75	75		24	21000	4779

IMPACT SOCKET WRENCHES 8 pans

1"



COD	AF	L	A	B	C	MINIMUM TIGHTENING TORQUE (lbf-in.)	MINIMUM TIGHTENING TORQUE (Nm/M)
56377	7/8"		50		15	8400	2847
56378	15/16"	60	52		18	9400	3186
56379	1"		54		18	10500	3558
56380	1.1/8"		59	54	19	12800	4338
56381	1.3/16"	62	61		21	14100	4779
56382	1.1/4"		63		21	15400	5220
56383	1.5/16"		66		22	16700	5661
56384	1.3/8"	65	68		22	18000	6102
56385	1.7/16"		71		24	19500	6609
56386	1.1/2"	67	73	58	24	21000	7119
56387	1.5/8"	70	78		24	24000	8136
56388	1.11/16"	74	82		27	26000	8814
56389	1.3/4"		84		27	27000	9153
56390	1.13/16"	76	86		30	28000	9492
56391	1.7/8"		88	62	30		
56392	2"	80	94		32		
56393	2.3/16"	84	101		35		

