

# 1000V INSULATED OFFSET HEAVY DUTY PIPE WRENCH

EGA Master insulated tools comply with IEC 60900 international standard, each one of the pieces being tested at 10,000V (10 times the voltage we certify).

They are also tested rigorously according to what the norms establishes: adherence test, impact test, flame propagation test and dielectric penetration test.



## MAIN APPLICATION FIELDS

Electrical installation	High Voltage networks	Electric maintenance
Power Plants	Low Voltage networks	Fire-fighters
Electric Stations and substations	Telecommunications	Lighting installation and repair

## CAUTION

- 1 Don't ever use tools under voltage if they present pores, fissures, encrusted elements or if the white insulation layer is visible.
- 2 **Insulating floors and safety shoes** are recommended to work under voltage.
- 3 **Avoid contact with water** while working under voltage.
- 4 **Do not ever touch directly any item that may be under voltage.** Use a voltage tester to check first.

# 1000V INSULATED OFFSET HEAVY DUTY PIPE WRENCH

The Heavy Duty wrenches from EGA Master are specially designed for the most demanding industrial applications such as mining, oil, aerospace and automotive industries.



**1.** Full floating forged hook jaw for **fast ratcheting action**.

**2.** **Graduations** on hook jaw show approximate size of opening for different pipe sizes.



**3.** Replaceable, **twice hardened alloy steel jaws**. Precision-milled, biased tooth design maximizes gripping strength and tool life.



**4.** Knurled adjustment nut for easy one-handed operation.

**5.** Large flange **prevents nut from being inadvertently rotated** when wrench is set down.




**6.** Extra large self-cleaning threads.



**7.** Wide gripping surface for **increased comfort**.

**8.** Anti-shock guards for maximum safety.

## 1000V OFFSET HEAVY DUTY PIPE WRENCH



COD.	L (inch)	A (mm)	B (inch)	C (mm)	Kg			
<b>76758</b>	8	16	1	20	0,4			
<b>76759</b>	10	20	1.1/2	23	0,9	6		
<b>76760</b>	12	22		26	1,4		●	
<b>76761</b>	14	25	2	29	1,6	5		
<b>76762</b>	18	27	2.1/2	33	2,4	3		-

△ 1000V | IEC 60900



### TECHNICAL SPECIFICATIONS

MATERIAL	Handle	Ductile cast iron (nodular)
	Heel jaw	Steel alloy
	Movable jaw	Cr-V
	Insulation	PVC
HARDNESS	Handle	120-160Hb
	Heel jaw	55-60 HRC
	Teeth of the movable jaw	55-60 HRC
FINISHING	Handle	Painted in Epoxy powder red color ral-2002 semi-texturized
	Heel & Movable jaw	Black finished
	Insulation	Orange