

PERFOMATICS

EGA Master's drills offer a range of high quality drills with sintered diamond drills specially designed to work in the construction sector.



1. Able to drill even most demanding materials: reinforced concrete, cement, bricks, asphalt, stones, granite, marble, etc.

2. With PRCD, Included to avoid voltage picks.

3. include the installation for the inflow of refrigerating water for wet cutting.

4. Ideal for drillings of up to 300mm diameters.

5. *The Soft Starting System.: This innovative and exclusive system makes it easy the start of drilling in walls, starting with slow speed for centring perfectly the beginning of the perforation. In this way, the System avoids undesired slips that can damage the wall or the floor.

* Only in references Perfomatic 80 y 102.

PERFOMATIC 80



COD	CAP	Ø	W	V	* R	R.P.M.	Kg.
60226				230V (50-60Hz)	1/2" BSP	950-	
60227	12-80		1500	110V (50-60Hz)	1.1/4" UNC	2100	7,5

* 1/2": Female - 1.1/4": Male
 SSR: Soft start system

PERFOMATIC 102

With soft start system



COD	CAP Ø	W	V	* R	R.P.M.	Kg.
60228	12-102	1500	230V (50-60Hz)	1/2" BSP	950-2100	22
60229			110V (50-60Hz)	1.1/4" UNC		

* 1/2": Female - 1.1/4": Male

SSR: Soft start system

PRCD: Included (to avoid voltage picks)

PERFOMATIC 205

With support for fast drilling of concrete, stone, brick...



COD	CAP Ø	W	V	* R	R.P.M.	L	L	∩	Kg.
60230	12-205	2400	230V 50-60Hz	1/2" BSP 1.1/4" UNC	600	•			41
60231							•		
60232							•	•	
60233							•	•	
60234							•		
60235						110V 50-60Hz	•		
60236							•	•	
60237			•	•					

* 1/2": Female - 1.1/4": Male

PRCD: Included (to avoid voltage picks)

Fixed bracket

90° reclinable bracket

Vacuum base

PERFOMATIC 255

With support for fast drilling of concrete, stone, brick...



COD	CAP Ø	W	V	* R	R.P.M.	L	L	∩	Kg.
60239	12-255	2600	230V 50-60Hz	1/2" BSP 1.1/4" UNC	460-900			•	45
60240								•	
60241								•	
60242						110V 50-60Hz	•		
60243							•		
60244							•	•	
60245			•	•					

* 1/2": Female - 1.1/4": Male

PRCD: Included (to avoid voltage picks)

PERFOMATIC 300

With support for fast drilling of concrete, stone, brick...



CE*G12

COD	CAP Ø	W	V	* R	R.P.M.	L				Kg.
60246							•			
60247			230V					•		
60248			50-60Hz	1/2"			•		•	
60249	12-300	3300		BSP	460-900		•		•	50
60250				1.1/4"			•			
60251			110V	UNC				•		
60252			50-60Hz				•		•	
60253								•	•	

* 1/2": Female -1.1/4": Male

PRCD: Included (to avoid voltage picks)

SINTERED DIAMOND DRILLS FOR REINFORCED CONCRETE DRILLS

For wet cut



COD A	Ø x L	R
64366	32x360	1.1/4" UNC
64367	44x360	
64368	53x360	
64369	63x360	
64370	71x360	
64371	83x360	
64372	89x360	
64373	102x360	
64374	110x360	
64375	120x360	
64376	127x360	
64377	132x360	
64378	150x360	
64379	159x360	
64380	166x360	
64381	180x360	
64382	202x360	
64383	220x360	
64384	244x360	
64385	300x360	
57100	32x450	FEMALE
57101	44x450	
57102	53x450	
57103	63x450	
57104	71x450	
57105	83x450	
57106	89x450	
57107	102x450	
57108	110x450	
57109	120x450	
57110	127x450	
57111	132x450	
57112	150x450	
57113	159x450	
57114	166x450	
57115	180x450	
57116	202x450	
57117	220x450	
57118	244x450	
57119	300x450	

COD B	Ø x L	R
64355	12x120	1/2" BSP
64356	18x220	
64357	26x320	
64358	32x320	
64359	44x320	
64360	53x320	
64361	63x320	
64362	71x320	
64363	83x320	
64364	89x320	
64365	102x320	

For dry cut



COD	Ø x L	R
64386	32x300	1/2" BSP MALE
64387	44x300	
64388	53x300	
64389	63x300	
64390	71x300	
64391	83x300	
64392	89x300	
64393	102x300	
64394	110x300	
64395	120x300	
64396	132x300	
64397	150x300	

FIXED BRACKET



COD		Kg.
64398	PERFOMATIC-205	22
	PERFOMATIC-255	
	PERFOMATIC-300	

90° RECLINABLE BRACKET



COD		Kg.
64399	PERFOMATIC-205	35
	PERFOMATIC-255	
	PERFOMATIC-300	

VACUUM BASE



COD		Kg.
64400	PERFOMATIC-205	6,5
	PERFOMATIC-255	
	PERFOMATIC-300	

EXTENSIÓN



COD	A-B	Ø x L	Kg.
64406	1.1/4" UNC	40x150	1,0
64407		40x210	1,3
64414	1/2" BSP	30x200	0,8
64415		30x260	1,1

MANGO



COD		Kg.
64408	PERFOMATIC-80	0,7
	PERFOMATIC-102	

CONECTOR ADAPTADOR ROSCA



COD	A-B	Kg.
64426	* 1.1/4" UNC - 1/2" BSP	0,4

* Female - Female

