

PNEUMATIC BELT SANDERS

EGA Master pneumatic band sanders are specially designed for **paint removal, sanding and finishing of small surfaces.**

360° turning adjustable handle

1. Low noise level.
2. Reduced air consumption.
3. 6,3 bar working pressure.
4. Speed control lever.
5. 360° turning adjustable handle adapts to any work position.
6. Handle exhaust removes air out of the work area.
7. Ideal size for delicate finishing work on small surfaces.
8. 3 Band included.



PNEUMATIC BELT SANDER 10X330



COD	BELT	R.P.M	← L →	Kg
57076	10x330mm	16000	260	0.9

Narrow body design makes possible its access into tight or confined spaces, while thin belt allows sanding in small or very precise zones.

TECHNICAL SPECIFICATIONS

Belt (3pcs)	10x330mm (1pc - 80gr / 2pcs - 120gr)
RPM	16000
Air consumption	80LPM (2.8CFM)
Air inlet	1/4"
Power	0.28 kW
Noise pressure level	82.4dBA
Noise power level	93.4dBA
Vibration	<2.5m/s ²
Working pressure	6,3bar / 90PSI
Ø int (mm)	3/8"
Belt 10x330mm	Cod. 87943 - 80gr Cod. 87944 - 120gr

PNEUMATIC BELT SANDER 20X520



COD	BELT	R.P.M	← L →	Kg.
57077	20x520mm	16000	340	1.2

Powerful motor enables working on hard metals.

TECHNICAL SPECIFICATIONS

Belt (3pcs)	20X520mm
RPM	16000
Air consumption	80LPM (2.8CFM)
Air inlet	1/4"
Power	0.373kW
Noise pressure level	84.4dBA
Noise power level	95.4dBA
Vibration	<2.5m/s ²
Working pressure	6,3bar / 90PSI
Ø int (mm)	3/8"
Belt 20x520mm	Cod. 87945

MATERIAL	Steel and Aluminium
-----------------	---------------------

