

OFFSET SLOGGING RING WRENCH



The EGA Master offset slogging ring wrenches are designed to tighten or loosen large bolts and nuts with the help of hammer or mallet in heavy industry, shipbuilding, industrial plant maintenance... etc.



From 22mm-7/8" to 135mm-5.1/16"!




1. To tighten or loosen large nuts and bolts in ship-building and other heavy industries, maintenance of industrial plants.

2. Suitable to be used with hammer or mallet.



3. Its design allows tightening and loosening nuts or screws that are at a lower level than the surrounding surface or in places of difficult access.





OFFSET SLOGGING RING WRENCH MM





COD.	L (mm)	AF mm	A (mm)	B (mm)	C (mm)	Kg		
55000		22						
55001	240	24	42	18	23	0,9		
55002	270	27		20	26	1,2		
55003	280	30	50	22	28	1,4		
55004	290	32	55	23	29	1,6	5	1
55005	300	36						
55006	300	38	65	25	31	1,8		
55007	320	41	70	26	32	2		
55008	340	46		27	34	2,6		
55009	350	50	80	32	38	3		
55010	360	55	85	33	39	3,9		
55011	380	60	90	35	41	4,0		
55012	390	65	95	38	44			
55013	400	70	105	41	47	5,0		
55014	420	75	110	43	49	5,5		
55015	440	80				7,0		
55016	460	85	125	45	50	7,5		
55017		90						
55018	480	95	140	47		9,0		
55019		100			55			
55020	520	105	155	49		11		
55021		110						
55022	550	115	170	50	60	12		
55023		120						
55024	590	125	180	55	64	14		
55025		130						
55026	620	135	200	60	70	16		

OFFSET SLOGGING RING WRENCH INCH.



COD.	L (mm)	 inch	A (mm)	B (mm)	C (mm)			
55027		7/8						
55028	240	15/16	42	18	23	0,9		
55029		1						
55030	270	1.1/16	50	20	26	1,2		
55031		1.1/8						
55032	280	1.3/16	22	28	1,4		5	1
55033		1.1/4						
55034	290	1.5/16	55	23	29	1,6		
55035		1.3/8						
55036	300	1.7/16	65	25	31	1,8		
55037		1.1/2						
55038		1.9/16						
55039	320	1.5/8		26	32	2		
55040		1.11/16	70					
55041		1.3/4						
55042	340	1.13/16		27	34	2,6		
55043		1.7/8						
55044	350	1.15/16	80	32	38	3		
55045		2						
55046		2.1/16						
55047	360	2.1/8	85	33	39	3,9		
55048		2.3/16						
55049		2.1/4						
55050	380	2.5/16	90	35	41	4,1		
55051		2.3/8						
55052		2.7/16						
55053		2.1/2						
55054	390	2.9/16	95	38	44	4,2		
55055		2.5/8						
55056		2.11/16						
55057	400	2.3/4	105	41	47	5,1		
55058		2.13/16						
55059		2.7/8						
55060	420	2.15/16	110	43	49	5,5		
55061		3						
55062	440	3.1/16				6,9		
55063		3.1/8						
55064		3.1/4	125	45	50			
55065	460	3.5/16				7,3		
55066		3.3/8						
55067		3.1/2						
55068		3.9/16						
55069	480	3.5/8	140	47		8,8		
55070		3.11/16						
55071		3.3/4						
55072		3.13/16			55			
55073		3.7/8						
55074		3.15/16						
55075	520	4	155	49		10,9		
55076		4.1/16						
55077		4.1/8						

OFFSET SLOGGING RING WRENCH INCH.



55078		4.3/16				
55079	520	4.1/4				
55080		4.5/16	170	50	60	12
55081		4.3/8				
55082	550	4.1/2				
55083		4.9/16				
55084		4.5/8				
55085		4.11/16				
55086	590	4.3/4	180	55	64	14
55087		4.13/16				
55088		4.7/8				
55089		4.15/16				
55090		5				
55091	620	5.1/4	200	60	70	16
55092		5.1/16				

TECHNICAL SPECIFICATIONS

MATERIAL	Chrome steel
GENERAL HARDNESS	Sinze from 22mm-7/8" to 46mm-1.3/4": 34 – 40 HRC Sinze from 50mm-1.13/16" to 135mm-5.1/16": 30 – 36 HRC
FINISHING	Painted in black color