

# STILLSON PIPE WRENCHES

EGA Master reinforced Stillson Pipe Wrenches are manufactured with forged special steel handles according to the norm **UNE-16552, BS 3594-1 y GGG-W-00651d**.



**1.** Double spring system for ratchet action, which facilitates the locking and the immediate releasing of the wrench and a quick continuation of the operation.




**2.** The teeth, heat treated, provide adequate wear resistance and a firm grip on all surfaces.



**3.** They are specially designed for the toughest uses in industries such as **mining or oil & gas**.

## STILLSON



COD	← L →	← A →	← B →	← C →	Kg.		
61001	8"	17	3/4"	12	0,3	1	1
61002	10"	23	1"	16	0,6		
61003	12"	24	1.1/4"	21	0,8		
61004	14"	28	1.1/2"	24	1,1		-
61005	18"	30	2"	27	1,9		
61006	24"	39	2.1/2"	30	3,1		
61007	36"	49	4"		6,5		




Unlimited guarantee




## TECHNICAL SPECIFICATIONS

MATERIAL	Handle	Ductile cast iron
	Jaw	
	Nut	Special steel
HARDNESS	Handle	35-45 HRC
	Teeth	55-60 HRC
	Nut	32-48 HRC
FINISHING	Handle	Painted in Epoxy powder red color ral-2002 semi-texturized
	Movable jaw and heel jaw	Black finished

UNE-16552 / BS 3594-1 / GGG-W-00651d US. FEDERAL SPECIFICATIONS

## SPARE PARTS

				
8"	80047	80040	80033	
10"	80048	80041	80034	
12"	80049	80042	80035	
14"	80050	80043	80036	
18"	80051	80044	80037	
24"	80052	80045	80038	
36"	80053	80046	80039	

 Spring Set  
 Nut  
 Hook Jaw