



Main

| | |
|---------------------------|--------------------------------------|
| Range | TeSys |
| Product name | TeSys GC |
| Product or component type | Modular contactor |
| Device short name | GC40 |
| Contacteur application | Lighting Motor control Heating |

Complementary

| | |
|---|--|
| Utilisation category | AC-7B AC-7A |
| Poles description | 2P |
| Pole contact composition | 2 NO |
| [Ue] rated operational voltage | <= 250 V AC |
| [Ie] rated operational current | 40 A AC-7A 15 A AC-7B |
| Operating position | 30°/Vertical |
| Control circuit type | AC at 60 Hz |
| [Uc] control circuit voltage | 220...240 V AC 60 Hz |
| [Uimp] rated impulse withstand voltage | 4 KV |
| [Ith] conventional free air thermal current | 40 A (at 50 °C) for power circuit |
| Irms rated making capacity | 120 A at 400 V AC for power circuit conforming to IEC 61095 |
| Rated breaking capacity | 120 A at 400 V for power circuit conforming to IEC 61095 |
| [Icw] rated short-time withstand current | 320 A 40 °C - 10 s for power circuit 100 A 40 °C - 30 s for power circuit |
| Associated fuse rating | 40 A gL at <= 440 V for power circuit |
| Average impedance | 2 MOhm - Ith 40 A 50 Hz for power circuit |
| [Ui] rated insulation voltage | 500 V conforming to IEC 61095 500 V conforming to VDE 0110 |
| Electrical durability | AC-7A: 100000 cycles AC-7B: 100000 cycles |
| Power dissipation per pole | 3.2 W |
| Control type | Remote control |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| Standards | IEC 60947-5 IEC 61095 |

| | |
|---------------------------------|--|
| Connections - terminals | Control circuit: screw clamp terminals 1 cable(s) 2.5 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 2.5 mm ² flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 2.5 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 1.5 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 1.5 mm ² solid without cable end Control circuit: screw clamp terminals 2 cable(s) 1.5 mm ² solid without cable end Power circuit: screw clamp terminals 1 cable(s) 25 mm ² flexible without cable end Power circuit: screw clamp terminals 2 cable(s) 16 mm ² flexible without cable end Power circuit: screw clamp terminals 1 cable(s) 16 mm ² flexible with cable end Power circuit: screw clamp terminals 2 cable(s) 4 mm ² flexible with cable end Power circuit: screw clamp terminals 1 cable(s) 25 mm ² solid without cable end Power circuit: screw clamp terminals 2 cable(s) 6 mm ² solid without cable end |
| Tightening torque | Control circuit: 0.8 N.m - on screw clamp terminals Power circuit: 2 N.m - on screw clamp terminals |
| Operating time | 10...25 ms opening 10...30 ms closing |
| Mechanical durability | 1000000 Cycles |
| Maximum operating rate | 300 Cyc/H 50 °C |
| Control circuit voltage limits | Drop-out: 0.2...0.75 Uc at 50 Hz (at <50 °C) Operational: 0.85...1.1 Uc at 50 Hz (at <50 °C) |
| Inrush power in VA | 34 VA 50 Hz (at 20 °C) |
| Hold-in power consumption in VA | 4.6 VA 50 Hz (at 20 °C) |
| Heat dissipation | 1.6 W at 50/60 Hz |

Environment

| | |
|---------------------------------------|--|
| IP degree of protection | IP40 conforming to VDE 0106 (in enclosure) IP20 conforming to VDE 0106 |
| Protective treatment | TC |
| Ambient air temperature for operation | -5...50 °C |
| Ambient air temperature for storage | -40...70 °C |
| Operating altitude | <= 3000 m |
| Mechanical robustness | Shocks contactor open: 10 Gn for 11 ms Shocks contactor closed: 15 Gn for 11 ms Vibrations contactor open: 2 Gn, 5...300 Hz Vibrations contactor closed: 3 Gn, 5...300 Hz |
| Total number of 18 mm modules | 2 |
| Height | 85 Mm |
| Width | 36 Mm |
| Depth | 62.5 Mm |
| Net weight | 0.23 Kg |
| Quantity per set | Set of 6 |
| Colour | White |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 233 G |
| Package 1 Height | 8 Cm |
| Package 1 width | 9.5 Cm |
| Package 1 Length | 23 Cm |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 6 |
| Package 2 Weight | 1.401 Kg |
| Package 2 Height | 8 Cm |
| Package 2 width | 9.5 Cm |
| Package 2 Length | 23 Cm |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 48 |
| Package 3 Weight | 11.897 Kg |
| Package 3 Height | 30 Cm |

| | |
|------------------|-------|
| Package 3 width | 30 Cm |
| Package 3 Length | 40 Cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

| | |
|-----------------------|-----------------------|
| Product Life Status : | Commercialised |
|-----------------------|-----------------------|