



### Main

|                           |                  |
|---------------------------|------------------|
| Range                     | Vivace           |
| Product or component type | Switched socket  |
| Device short name         | KB25             |
| Device presentation       | Complete product |

### Complementary

|                              |   |
|------------------------------|---|
| Outlet poles configuration   | 2P + E  |
| Number of gangs              | 2 gangs   |
| Colour tint                  | White   |
| Material                     | Polycarbonate: grid plate<br>Polycarbonate: surround<br>Polycarbonate: base |
| Projecting depth             | 8 Mm  |
| Device mounting              | Flush   |
| Mounting support             | Wall mounted  |
| Fixing mode                  | By screw M3.5   |
| Fixing center                | 120.6 mm  |
| Embedding depth              | 35 Mm   |
| Rated current                | 13 A at 250 V AC, resistive   |
| Network frequency            | 50 Hz   |
| Contacts material            | Brass and phosphor bronze   |
| Connections - terminals      | Pillar terminal   |
| Terminal identifier          | L<br>N<br>Earth   |
| Tightening torque            | 0.4 N.M   |
| Clamping connection capacity | 3 x 2.5 mm <sup>2</sup><br>2 x 4 mm <sup>2</sup>                            |
| Width                        | 147 Mm  |
| Height                       | 87 Mm   |

### Environment

|                                       |                               |
|---------------------------------------|-------------------------------|
| Standards                             | SS 145<br>MS 589<br>BS 1362-2 |
| Ambient air temperature for operation | -5...40 °C                    |
| Relative humidity                     | 0...95 %                      |
| Environmental characteristic          | Indoor use                    |

### Packing Units

|                  |           |
|------------------|-----------|
| Package 1 Weight | 138.000 G |
| Package 1 Height | 1.000 Cm  |
| Package 1 width  | 1.000 Cm  |
| Package 1 Length | 1.000 Cm  |

### Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product                         |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>                           |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a> |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Product Life Status : **Commercialised**