



Main

Range	Vivace
Device short name	KB30
Product or component type	Fuse connection unit
Device presentation	Complete mechanism

Complementary

Cover frame colour tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Projecting depth	8 Mm
Device mounting	Surface
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	35 Mm
Rated current	13 A at 250 V AC, resistive
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	Pillar terminal
Terminal identifier	L out N out L in N in Earth
Tightening torque	0.4 N.M
Clamping connection capacity	2 x 4 mm ² incoming 3 x 2.5 mm ² incoming 1 x 1.5 mm ² outgoing 1 x 2.5 mm ² input
Width	87 Mm
Height	87 Mm

Environment

Standards	BS 1363-4
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	116.9 G
Package 1 Height	8.6 Cm
Package 1 width	3.5 Cm
Package 1 Length	14.6 Cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	1.239 Kg
Package 2 Height	9.5 Cm
Package 2 width	15 Cm
Package 2 Length	19 Cm
Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Weight	11940 G
Package 3 Height	210 Mm
Package 3 width	315 Mm
Package 3 Length	500 Mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**