



### Main

Device short name	KB31
Product or component type	Keycard switch
Device presentation	Complete mechanism

### Complementary

Number of gangs	1 gang
Cover frame colour tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Projecting depth	8 Mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	35 Mm
Rated current	16 A at 220...240 V AC, resistive load
Network frequency	50/60 Hz
Connections - terminals	Pillar terminal
Terminal identifier	L N
Tightening torque	0.4 N.M
Width	86 Mm
Height	86 Mm

### Environment

Standards	IEC 60669-2-1
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	0...60 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

### Packing Units

Package 1 Weight	129.000 G
Package 1 Height	1.000 Cm
Package 1 width	1.000 Cm
Package 1 Length	1.000 Cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

### Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status :	<b>Commercialised</b>
-----------------------	-----------------------