



Main

Range	Vivace
Product or component type	Switch
Device short name	KB31
Device application	Control
Device presentation	Complete mechanism

Complementary

Switch function	Intermediate
Actuator	Rocker
Number of gangs	1 gang
Colour tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Nylon: base
Projecting depth	8 Mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	35 Mm
Rated current	10 A at 250 V AC, fluorescent
[Ue] rated operational voltage	250 V AC
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	Pillar terminal
Terminal identifier	L2 L1
Tightening torque	0.4 N.M
Clamping connection capacity	<= 2.5 mm ²
Width	86 Mm
Height	86 Mm

Environment

Standards	SS 227 IEC 60669-1 MS IEC 60669-1
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

Packing Units

Package 1 Weight	82.500 G
Package 1 Height	1.000 Cm
Package 1 width	1.000 Cm
Package 1 Length	1.000 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**