



Main

Range	Vivace
Device short name	KB31
Product or component type	Speed controller
Device presentation	Complete mechanism
Cover frame colour tint	White

Complementary

Power range	Motor: 250 VA
[Ue] rated operational voltage	220...240 V AC
Network frequency	50 Hz
Number of gangs	1 gang
Connections - terminals	Pillar terminals
Terminal identifier	L Load
Tightening torque	0.4 N.M
Clamping connection capacity	1.5 mm ²
Contacts material	Brass and phosphor bronze
Material	Polycarbonate: grid plate Polycarbonate: surround Nylon: base
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Width	87 Mm
Height	87 Mm
Projecting depth	8 Mm
Embedding depth	35 Mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

Packing Units

Package 1 Weight	93.000 G
Package 1 Height	1.000 Mm
Package 1 width	1.000 Mm
Package 1 Length	1.000 Mm

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
-------------------	--

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**