



### Main

Range of product	Vivace
Device short name	KB31
Product or component type	TVF socket
Device presentation	Complete mechanism

### Complementary

Number of gangs	1 gang
Number of outputs	1
Cover frame colour tint	White
Material	Polycarbonate: surround Polycarbonate: grid plate Polycarbonate: base
Projecting depth	8 Mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	35 Mm
Connections - terminals	Clamp terminal
Tightening torque	0.4 N.M
Width	87 Mm
Height	87 Mm

### Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

### Packing Units

Package 1 Weight	45.780 G
Package 1 Height	1.000 Mm
Package 1 width	1.000 Mm
Package 1 Length	1.000 Mm

### Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**