Product data sheet Characteristics

KB31/1

Vivace - 16AX 250V 1Gang 1Way Switch - white







Main

Range	Vivace	
Product or component type	Switch	
Device short name	KB31	
Device application	Control	
Device presentation	Complete mechanism	
Switch application	Switch	

Complementary

Complementary	
Switch function	1-way
Actuator	Rocker
Number of gangs	1 gang
Colour tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Projecting depth	8 Mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	35 Mm
Rated current	16 AX at 250 V AC, inductive 16 AX at 250 V AC, fluorescent
[Ue] rated operational voltage	250 V AC
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	Pillar terminal
Terminal identifier	COM L1
Tightening torque	0.4 N.M
Clamping connection capacity	2.5 mm²
Width	87 Mm
Height	87 Mm

Environment

Standards	MS IEC 60669-1 SS 227 IEC 60669-1
Ambient air temperature for operation	-540 °C
Relative humidity	095 %
Environmental characteristic	Indoor use

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	79.38 Kg	
Package 1 Height	21 Cm	
Package 1 width	31.5 Cm	
Package 1 Length	50 Cm	

Offer Sustainability

Green Premium product	
☑ REACh Declaration	
Compliant EEU RoHS Declaration	
Yes	
€Yes	
☐ China RoHS Declaration	
Product Environmental Profile	
	Compliant EVEU RoHS Declaration Yes China RoHS Declaration

Product Life Status : Commercialised

