



### Main

Range	Vivace
Device short name	KB32
Product or component type	Data socket
Device presentation	Complete mechanism
Cover frame colour tint	White

### Complementary

Communication network category	5
Number of gangs	2 gangs
Tightening torque	0.4 N.M
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Width	87 Mm
Height	87 Mm
Projecting depth	8 Mm
Embedding depth	35 Mm

### Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	100.6 G
Package 1 Height	8.6 Cm
Package 1 width	5 Cm
Package 1 Length	8.6 Cm
Unit Type of Package 2	BB1
Number of Units in Package 2	8

Package 2 Weight	875 G
Package 2 Height	15 Cm
Package 2 width	19 Cm
Package 2 Length	8 Cm
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Weight	8300 G
Package 3 Height	210 Mm
Package 3 width	315 Mm
Package 3 Length	500 Mm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**