



Main

Range	Vivace
Device short name	KB32
Product or component type	Data socket with shutter
Device presentation	Complete mechanism
Cover frame colour tint	White

Complementary

Communication network category	6
Number of gangs	2 gangs
Tightening torque	0.4 N.M
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Width	86 Mm
Height	86 Mm
Projecting depth	8 Mm
Embedding depth	35 Mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
Standards	FCC

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	100.4 G
Package 1 Height	8.6 Cm
Package 1 width	5 Cm
Package 1 Length	8.6 Cm
Unit Type of Package 2	BB1

Number of Units in Package 2	8
Package 2 Weight	873 G
Package 2 Height	15 Cm
Package 2 width	19 Cm
Package 2 Length	8 Cm
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Weight	8280 G
Package 3 Height	210 Mm
Package 3 width	315 Mm
Package 3 Length	500 Mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**