



### Main

Product or component type	Shaver socket
Device short name	KBT
Device presentation	Complete mechanism

### Complementary

Number of gangs	2 gangs
Cover frame colour tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Projecting depth	8 Mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	120.6 mm
Embedding depth	47 Mm
Input voltage	240 V AC AC
Output voltage	115 V AC
Network frequency	50 Hz
Connections - terminals	Pillar terminal
Terminal identifier	L N E
Tightening torque	0.4 N.M
Clamping connection capacity	2.5 mm <sup>2</sup>
Width	146 Mm
Height	86 Mm

### Environment

Standards	IEC 61558-2-5
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
IP degree of protection	IP21

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**