



Main

Range	TeSys
Product name	TeSys K
Product or component type	Time delay auxiliary contact block
Device short name	LA1
Range compatibility	TeSys K LC1K TeSys K CA2K TeSys K CA3K TeSys K CA4K
Mounting location	Front
Pole contact composition	1 C/O
Auxiliary contacts operation	Time delay
Timer type	On delay
Time delay range	1...30 s
[Ue] rated operational voltage	110...240 V AC for control circuit 240 V AC for signalling circuit
Rated operational voltage limits	0.85...1.1 U _c
[I _{th}] conventional free air thermal current	2 A for signalling circuit
Standards	EN/IEC 60947-5-1 UL 60947-5-1 CSA C22.2 No 60947-5-1

Complementary

Reset time	1.5 S during time delay 0.5 S after time delay
Insulation resistance	> 10 MOhm
Connections - terminals	Slip-on terminals
Height	27 Mm
Width	38 Mm
Depth	38 Mm
Net weight	0.04 Kg


Environment

Environmental characteristic	Normal environment
IP degree of protection	IP20 conforming to IEC 60529
Protective treatment	TC conforming to IEC 60068
Ambient air temperature for operation	-10...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	43.4 G
Package 1 Height	4.8 Cm
Package 1 width	4.8 Cm
Package 1 Length	5 Cm
Unit Type of Package 2	S02
Number of Units in Package 2	70
Package 2 Weight	3.361 Kg
Package 2 Height	15 Cm
Package 2 width	30 Cm
Package 2 Length	40 Cm

Offer Sustainability

EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Product Life Status : Commercialised
