



Commercial status

End of Commercialisation : JUL 25, 2021

△ End of Commercialisation

Main

Range	VarPlus
Device short name	DR
Product or component type	Detuned reactor
Network frequency	60 Hz
Reactive power rating	100 Kvar for 400 V AC 60 Hz
Network rated voltage	400 V AC 60 Hz
Tuning order	2.7 - 162 Hz - 14 % - 60 Hz

Complementary

Power losses	600 W
Value of inductance	0.676 MH
Inductance tolerance	- 5 % to 5 % per phase
Fundamental current rating	144.3 A
Maximum current Irms	147.2 A
Electrical insulation class	Class H
[Ui] rated insulation voltage	1.1 KV
Dielectric test voltage	4 KV 60 Hz 1 minute
[Imp] maximum permanent current	1.12 x I1
Harmonic current spectrum	5.5 % x I3 10.7 % x I5 5.3 % x I7 2.1 % x I11
Dynamic withstand current	2.2 x Isc
[Ith] conventional free air thermal current	2 A at 250 V AC 50 Hz
Type of installation	Indoor installation
Type of cooling	Forced convection
Connections - terminals	Pad terminal
Fixing center	200 x 125 mm
Height	350 Mm
Width	350 Mm
Depth	220 Mm
Net weight	54 Kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Standards	IEC 60068
IP degree of protection	IP00
Operating altitude	<= 2000 m
Ambient air temperature for operation	0...55 °C at <= 1000 m 0...50 °C at > 1000...2000 m
Average ambient air temperature for operation	50 °C at <= 1000 m (average over 24 hours) 40 °C at <= 1000 m (average over 1 year) 45 °C at > 1000...2000 m (average over 24 hours) 35 °C at > 1000...2000 m (average over 1 year)
Climatic withstand	Relative humidity: 20...80 % Salt mist (400 V/50 Hz) : 250 hours

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	61 Kg
Package 1 Height	58 Cm
Package 1 width	40 Cm
Package 1 Length	60 Cm
Unit Type of Package 2	P06
Number of Units in Package 2	2
Package 2 Weight	130.5 Kg
Package 2 Height	50 Cm
Package 2 width	80 Cm
Package 2 Length	60 Cm

Product Life Status : **End of commerc. announced**