



Main

Range of product	Merten inserts
Product or component type	Switch
Device presentation	Mechanism

Complementary

Switch function	1-pole 2-way
Actuator	Rocker
Device mounting	Flush
Fixing mode	By screws and claws
[Ue] rated operational voltage	250 V
Rated current	10 AX
Maximum switching current	10 A
Number of rocker	2
Connections - terminals	Screwless terminals
Material	Metal Plastic

Environment

IP degree of protection	IP20
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	67 G
Package 1 Height	3.7 Cm
Package 1 width	7.1 Cm
Package 1 Length	7.1 Cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	790 G
Package 2 Height	18 Cm
Package 2 width	9 Cm
Package 2 Length	27 Cm
Unit Type of Package 3	S03
Number of Units in Package 3	60

Package 3 Weight	5.2 Kg
Package 3 Height	30 Cm
Package 3 width	30 Cm
Package 3 Length	40 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**