



Main

Range	Actassi
Product or component type	Power distribution rail
Device application	Multi-purpose
Outlet standard description	Displaced earth
Accessory / separate part category	Current distribution accessory
Outlet poles configuration	2P + E with shutters
Quantity per set	Set of 1
Colour	Aluminium

Complementary

Device composition	1 power rail fixing elements
Ground lug position	90° ground lug
Socket number	7
[In] rated current	13 A
[Ue] rated operational voltage	240 V AC
Mounting support	Upright 19" rack
Fixing mode	By brackets Direct fixing
Material	Polyamide 6 with 30 % fibre glass
Surface finish	Anodized
Electrical connection	3 M power cord H05VV-F3G1.5
Number of rack unit	1U
Width	482.60 Mm
Depth	44 Mm

Environment

IP degree of protection	IP20 conforming to IEC 60529
Fire resistance	850 °C
Quality labels	UK

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.136 Kg
Package 1 Height	52 Cm
Package 1 width	9 Cm
Package 1 Length	8 Cm

Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Product Life Status : **Commercialised**