Product data sheet Characteristics

NSYSF20660M

Spacial SF compartmentalised enclosure - assembled - 2000x600x600 mm





Main

Range	Spacial	
Product name	Spacial SFM	
Device application	Compartmentalised application	
Product or component type	Suitable enclosure	
Enclosure nominal height	2000 Mm	
Enclosure nominal width	600 Mm	
Enclosure nominal depth	600 Mm	
Enclosure mounting	Floor-standing	
Product specific application	Insulating the control of a device Reduce the destructive effects of a short-circuit	
Device composition	1 structure 1 rear panel 1 roof 2 intermediate crossbars 2 panels for modularity: top and bottom	

Complementary

Structure type	Vertical uprights joined with top and bottom frames	
	Perforated structure with a pitch of 25 mm	
	Formed from a single section	
	Panels and doors built into the structure	
Mounting plate description	Without mounting plate	
Type of gland plate	Without gland plate	
Accessibility for operation	Rear	
, ,	Front	
	Sides of enclosure	
Removable parts	Rear panel by screws	
	Roof by screws	
Material	Frame: galvanised steel	
	Uprights: galvanised steel	
	Panels: sheet steel	
	Hinge: zamak	
Surface finish	Epoxy-polyester powder	
Colour	Grey (RAL 7035)	

Environment

Standards IEC 62208		IEC 62208	
---------------------	--	-----------	--

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	66 Kg
Package 1 Height	213 Cm
Package 1 width	64.5 Cm
Package 1 Length	69 Cm

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

Warranty	18 months

Product Life Status : Commercialised