



Overview

Lead time	Usually Ships within 4 Weeks
-----------	------------------------------

Main

Range	Spacial
Accessory / separate part category	Lifting accessory
Product or component type	Lifting eye
Device application	Multi-purpose
Mounting location	Enclosure top
Mounting support	Directly in the axis of the uprights
Range compatibility	Spacial SF Spacial SFHD Prisma PH Spacial SFM
Device composition	4 eyebolt
Quantity per set	Set of 1

Complementary

Material	Cast steel
Surface finish	Galvanized
Fixing mode	Screwed
Permanent permissible load	340 Kg for 1 eyebolt vertical direction
Height	62.5 Mm
Width	55 Mm
Depth	24 Mm
Diameter	29 Mm
ISO thread	M12

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	771 G
Package 1 Height	6 Cm
Package 1 width	10 Cm
Package 1 Length	10.5 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**