Product data sheet Characteristics

NSYSPF8100

Spacial SF/SM front plinth - 100x800 mm





Overview Lead time

Main		
Range	Spacial	
Accessory / separate part category	Enclosure accessory	
Product or component type	Plinth front	
Device application	Electronic application Compartmentalised application Multi-purpose	
Enclosure nominal dimensions	-	
Device composition	Fixing elements 4 corner cover 1 front panel 1 rear panel 4 corner	
Range compatibility	Spacial SF Spacial SM Spacial SD Spacial S3D Spacial CRN	
Mounting support	Plinth side panels	

Usually Ships within 4 Weeks

Complementary

Complementary	
Fixing mode	By fixing element - on structure location
Colour	Grey (RAL 7022)
Surface finish	Epoxy-polyester powder
Permanent permissible load	1300 Kg
Height	100 Mm
Width	800 Mm nominal:

Environment

IP degree of protection	IP30 (complete plinth)
IK degree of protection	IK10

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	5.201 Kg
Package 1 Height	11 Cm
Package 1 width	20.5 Cm
Package 1 Length	81.5 Cm
Unit Type of Package 2	P12
Number of Units in Package 2	56
Package 2 Weight	303.256 Kg
Package 2 Height	103 Cm
Package 2 width	80 Cm
Package 2 Length	120 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
Sustainable offer status	Green Fremum product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : Commercialised