



### Main

Range	Actassi
Product name	Actassi VDA
Product or component type	19" enclosure
Device application	Cabling
Product specific application	To protect network connectivity equipment To mount 19" equipment
Enclosure type	Network Cabinet
Provided equipment	2 x 19" uprights recessed of 120 mm from the front (pitch 25 mm)
Type of front cover	Glazed door
Door type	Front glazed door - with 1 point locking system (key: 333) - reversible opening at 180 °
Accessibility for operation	Top Front Side Rear
Removable parts	Front door removable toolless Top blanking plate Bottom blanking plate Side panels removable toolless Rear panel removable toolless
Colour tint	Door: light grey (RAL 7035) Panels: light grey (RAL 7035) Top and bottom: light grey (RAL 7035) Structure: dark grey (RAL 7011)

### Complementary

Device composition	1 x glazed door front 2 x panels side 2 x 19" uprights front 1 x assembled structure CBLX torx 1 x roof with removable blanking plate top 1 x panel rear 4 x levelling feet
Permanent permissible load	400 Kg static 250 Kg dynamic
Type of rear cover	Panel
Type of side panel	Panel
Number of cut-out	1 cut-outbottom 1 cut-outtop side panel 1 cut-outtop - split in 3 parts
Enclosure mounting	Floor-standing

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Material	Sheet steel: structure Sheet steel: door Sekurit glass: door Galvanized steel: upright Sheet steel: panel
Surface finish	Epoxy-polyester powder
Width	800 Mm
Height	2000 Mm
Depth	1000 Mm
Net weight	119 Kg
Number of rack unit	42U
Targeted region	Europe

### Environment

IK degree of protection	IK08 conforming to IEC 62262
IP degree of protection	IP20 conforming to IEC 60529
Standards	EIA-310D IEC 60297-3-100

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	118.7 Kg
Package 1 Height	212 Cm
Package 1 width	84 Cm
Package 1 Length	104 Cm
Unit Type of Package 2	PAL
Number of Units in Package 2	1
Package 2 Weight	118.7 Kg
Package 2 Height	212 Cm
Package 2 width	84 Cm
Package 2 Length	104 Cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**