## Product data sheet Characteristics

## VW3A3725

# BACnet MS/TP communication module - Altivar Process ATV600



#### Main

Range of product	Altivar
Product or component type	Communication module

#### Complementary

Range compatibility	Altivar Process Modular
3	Altivar Process ATV600
Product compatibility	ATV600
Communication port protocol	BACnet MS/TP
Electrical connection	Screw terminal block 5-pin removable terminal block, BACnet MS/TP
Transmission rate	9.6, 19.2, 38.4, 76.8 kbit/s
Transmission support medium	2 twisted pairs
Communication service	AV, BV, MSV for BACnet MS/TP COV notification
Communication network type	RS485
Display type	1 LED for error 1 LED for transmission activity 1 LED for reception activity (RX) 1 LED for module status
Net weight	0.035 Kg

#### Environment

IP degree of protection	IP20
Ambient air temperature for operation	-2065 °C
Ambient air temperature for storage	-2570 °C
Relative humidity	595 % without condensation
Operating altitude	02000 m
Storage altitude	03048 M
Vibration resistance	1.5 mm (f = 313 Hz) 1 mm (f = 1323 Hz) 2 gn (f = 13150 Hz)
Shock resistance	15 gn for 11 ms

Electromagnetic compatibility	EMC immunity conforming to EN/IEC 61000-6-1
	EMC immunity level 2 conforming to EN/IEC 60730-1
	Electrostatic discharge level 3B conforming to IEC 61000-4-2
	Radiated RF fields level 3A conforming to IEC 61000-4-3
	Electrical fast transient/burst immunity test level 4B conforming to IEC 61000-4-4
	Surge immunity test level 3 conforming to IEC 61000-4-5
	Conducted RF disturbances level 3A conforming to IEC 61000-4-6
	Conducted EMC level 2 conforming to EN/IEC 60730-1
	Conducted EMC conforming to EN/IEC 61000-6-3
Product certifications	BTL
	CSA
	UL 508
	UL 873

### Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	64 G	
Package 1 Height	4.5 Cm	
Package 1 width	6.2 Cm	
Package 1 Length	8.8 Cm	
Unit Type of Package 2	S03	
Number of Units in Package 2	100	
Package 2 Weight	6.871 Kg	
Package 2 Height	30 Cm	
Package 2 width	30 Cm	
Package 2 Length	40 Cm	

### Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	China RoHS Declaration

Product Life Status : Commercialised

