XZCP1141L2

Pre wired connectors XZ, straight female, M12, 4 pins, cable PUR 2 m





Main

Range of product	Telemecanique Cabling components	
Accessory / separate part category	Cabling accessory	
Accessory / separate part type	Pre-wired connectors	
Series name	General purpose	

Complementary

Electrical connection	Straight female connector M12, 4 pins
Cable connector fixing	Screw-on
Collar material	Metal
Status LED	Without
Cable length	2 M
Cable outer diameter	5.2 Mm
Cable composition	4 x 0.34 mm²
Wire insulation material	PUR
[Ue] rated operational voltage	250 V AC 300 V DC
[In] rated current	4 A
Contact resistance	5000 MOhm
Minimum insulating resistance	1 GΩ
Net weight	0.09 Kg

Environment

IP degree of protection	IP69K	
	IP65	
	IP67	
	IFO?	
Product certifications	CULus	
	00240	
Ambient air temperature for operation	-4080 °C static	
	-580 °C flexing	
	-580 Cilexing	
Ambient air temperature for storage	-4080 °C	
Ambient all temperature for storage	7050	

Packing Units

1
74 G
3.4 Cm
23.5 Cm

Package 1 Length	29.2 Cm
Unit Type of Package 2	S02
Number of Units in Package 2	40
Package 2 Weight	3.235 Kg
Package 2 Height	15 Cm
Package 2 width	30 Cm
Package 2 Length	40 Cm
Unit Type of Package 3	P06
Number of Units in Package 3	640
Package 3 Weight	60.26 Kg
Package 3 Height	77 Cm
Package 3 width	80 Cm
Package 3 Length	60 Cm

Offer Sustainability


Green Premium product
Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS Declaration
Yes
₽¥Yes
☐ Product Environmental Profile
☐ End Of Life Information

Contractual warranty

Warranty	18 months



Dimensions




L: Lenght of cable

Product data sheet Connections and Schema

XZCP1141L2

Connections and Schemes

Connector



BN: Brown BK: Black BU: Blue WH: White

Product Life Status: Commercialised